

Structural Connections Infrastructure Products



MB Bowco Duct Terminator

Precision Utility Precast Connections

Overview

MB Bowco Duct Terminators play a vital role in connecting PVC electrical ducts with a secure and watertight seal within precast concrete structures. Leviat offers precision-manufactured

For wider precast manholes and vaults, Leviat offers pre-assembled extended terminators. Terminator locators are also available for locating duct terminators in concrete vault walls.

terminators in a range of sizes to cater

to your specific requirements.

When casting thicker walls or larger panel dimensions, MB Bowco Duct Terminators can be expertly assembled into brackets, creating custom panels. This service streamlines the manufacturing process, reducing labor requirements at the plant.

Leviat's custom panel system is available for most standard sizes, providing versatility to accommodate various configurations.

Features

• Easy Installation: 6" or 8" centerto-center bracket intervals eliminate the need for drilling forms to install terminator locators.

Also available is a terminator bracket, specifically engineered to position terminators at 6" or 8" center-to-center intervals for special or custom applications.

- Concrete Protection: All sizes are available with a flexible seal ring designed to serve two important functions:
 - Prevent concrete from infiltrating the terminator opening during casting
 - Provide a smooth edge for seamless cable pulling operations, ensuring ease and efficiency











MB Bowco Duct Terminator

Precision, Watertight Utility Precast Connections





Product Data - MB Bowco Duct Terminator

Item Number	ID - Inside Diameter	H - Height	SCH 80	SCH 80 Outside Diameter	SCH 40	SCH 40 Outside Diameter	SCH 32.5	SCH 32.5 Outside Diameter
T2000	2.38″	2.39″	2	2.375″	2	2.375″	2	2.303″
T2001	2.38″	3.45″	2	2.375″	2	2.375″	-	-
T2534	2.4"	5.5″	2	2.375″	2	2.375″	-	-
T3000	3.51"	3"	3	3.5″	3	3.5″	3	3.388″
T3001	3.51"	3.43″	3	3.5″	3	3.5″	-	-
T3534	3.52″	5.5″	3	3.5″	3	3.5″	-	-
T4350	4.36″	3.43″	-	-	-	-	-	-
T4000	4.51″	3"	4	4.5″	4	4.5″	4	4.358″
T4501	4.51″	3.43″	4	4.5″	4	4.5″	-	-
T4504	4.51″	2.5″	4	4.5″	4	4.5″	-	-
T4534	4.51″	5.5″	4	4.5″	4	4.5″	-	-
T5000	5.57"	2.22"	5	5.563"	5	5.63"	5	5.391"
T5001	5.57"	3.43″	5	5.563"	5	5.63"	-	-
T5534	5.57"	5.64″	5	5.563"	5	5.63"	-	-
T5434	5.57"	4.5″	5	5.563"	5	5.63"	-	-
T6000	6.63″	3.43″	6	6.625″	6	6.25″	6	6.424″
T6534	6.64″	5.5″	6	6.625″	6	6.25″	-	-
T6734	6.64″	7.5″	6	6.625″	6	6.25″	-	-
*T8000	8.63″	5.75″	7	8.625	7	8.625"	7	8.355″

* Seal ring not included